

## Certificate of conformity of the factory production control 0432-CPR-00056-01 (EN)

Version 03

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

### Hot rolled long products of structural steels

Usage: **Steel structures, metal/concrete composite structures, high-rise structures and civil engineering structures**

*(product form, dimension range and steel grades: see Table 1, Annex 1)*

placed on the market under the name or trade mark of

#### Peiner Träger GmbH

Gerhard-Lucas-Meyer-Straße 10  
DE-31226 Peine

and produced in the manufacturing plant(s)

#### Peiner Träger GmbH

Gerhard-Lucas-Meyer-Straße 10  
31226 Peine

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in annex ZA of the standard(s)

### EN 10025-1:2004

under **system 2+** are applied and that

**the factory production control is assessed to be in conformity with the applicable requirements.**

This certificate was first issued on 28.11.2013 and will remain valid until 21.11.2028 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Dortmund, 22.11.2023

by order



Dipl.-Ing. Tenbusch  
Deputy Head of Certification Body (Dep. 21)



This Certificate consists of 1 page and 1 annex(es).

This Certificate replaces the Certificate no. 0432-CPR-00056-01  
dated 27.11.2018, Version 02.

The original of this document was issued in German language.  
In case of doubt only the German version is valid.

second copy

Table 1: product form, dimension range and steel grades:

<b>product form:</b>	<ul style="list-style-type: none"> <li>– Hot rolled I-, H- und U-shaped profiles</li> <li>– Flat steel and wide flange beam</li> </ul>
<b>dimension range:</b>	<ul style="list-style-type: none"> <li>– I- and H-shaped products:    Web height of    100 to 1100 mm</li> <li>– U-shaped products:            Web height of     80 to 400 mm</li> </ul>
<b>steel grades:</b>	<ul style="list-style-type: none"> <li>– S235JR, S235J0, S235J2, S275JR, S275J0, S275J2, S355JR, S355J0, S355J2, S355K2 according to EN 10025-2</li> <li>– S275N, S275NL, S355N, S355NL, S420N, S420NL, S460N, S460NL according to EN 10025-3</li> <li>– S275M, S275ML, S355M, S355ML, S420M, S420ML, S460M, S460ML according to EN 10025-4</li> <li>– S235J0W, S235J2W, S355J0WP, S355J2WP, S355J0W, S355J2W, S355K2W according to EN 10025-5</li> </ul>

second copy